



SCREENPASTE (SPA053)

Main Characteristics

Product Characteristics

Paste/Cream colour

Instruction for use

- Apply Screensolve (1 part) to the screen with a rag and add Screenpaste (1 part) to both sides of the mesh using a brush.
- Mix the two products in a circular motion, working the mixture into the screen.
- Allow the screen to stand for 15 minutes.
- Longer periods can damage polyester mesh.
- Rinse off thoroughly with water before using a high-pressure water gun and allow the screen to dry.

Features

- For removing stains from most type of mesh.
- Use with screensolve help remove of ghost images and other stains caused by screen printing inks.
- Convenient to use.
- Enhanced performance when use with Screensolve.

Standard Packing

25 Kg, 5 Kg and 1 Kg

Safety and Handling

- Is free from any toxic, carcinogenic, mutagenic and reprotoxic chemicals.
- Does not have a flashpoint and is, therefore, exempt from the Highly Flammable Liquid Regulations.
- SPA053 should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- SPA053 contains sodium hydroxide. It is corrosive and can cause severe burns. Avoid spashing and if skin contact occurs, irrigate the area with plenty of water.
- Should be stored away from children.
- Comprehensive information on *the Safety and Handling of Screenpaste* in Chaiyaboon Material Safety Data Sheet.

Storage

- Screenpaste should be stored in a cool dry place at 0–35 °C.
- SPA053 can be stored for 36 months.

