



SCREENPREP (SPR035)

Main Characteristics

Product Characteristics

Paste/Gray colour

Instruction for use

- Soak the screen with water.
- Use the soft brush to apply some of the Screenprep onto the screen mesh and rub in a circular manner.
- Ensure that the Screenprep is thoroughly applied to the entire surface on both sides of the mesh.
- Use a strong water jet or high-pressure gun to remove the Screenprep.
- Ensure the product is completely removed.
- Screenprep is normally applied once to remove grease from newly stretched screen.
- For better removal of grease, use Degreaser P-6419 each time after applying Screenprep.
- Dry the screen.

Important

- Stir well before use.

Features

- For grease removal and pre-treatment of all types of new mesh.
- The surface of the mesh is gently roughened to allow better adhesion of the emulsion.

Standard Packing

1 Kg

Safety and Handling

- Is free from any toxic, carcinogenic, mutagenic and reprotoxic chemicals.
- Does not have a flashpoint and is, therefore, exempt from the Highly Flammable Liquid Regulations.
- SPR035 should be used with care. Wear suitable PPE, for example, appropriate gloves and glasses.
- Should be stored away from children.
- Comprehensive information on *the Safety and Handling of Screenprep* in Chaiyaboon Material Safety Data Sheet.

Storage

- Screenprep should be stored in a cool dry place at 0–35 °C.
- SPR035 be stored for 36 months.



CHAIYABOON
— inKnovation —