



Screenfix SFX007

Page 1/2

Characteristics :

- Light yellow liquid.

Properties :

- Convenient use, economical cost.
- Good smoothness, fast drying, easy operation.
- Fabrics keep high tension after stretching.

Applications :

- For fixing all types of screen mesh to wooden or metal frames.

Method of Applications :

- Customers can dilute SFX007 with solvent depending on use conditions.
- Check the smoothness of the frame, stretch the fabric and use a brush to coat the adhesive.
- Remove the old adhesive on the frame before re-using.

Notes :

- Keep the container closed to avoid solvent loss, store in cool, dark and ventilated place.
- SFX007 contains volatile solvent, wear protecting gloves and gauze mask when using. Good ventilation is also necessary when using SFX007

STANDARD PACKING

Screenfix is available in the following pack size:

SFX007/1 1 ltr Screenfix

STORAGE

Screenfix should be cool dry area (above 0°C) away from direct sunlight. Containers should be tightly closed immediately after use.

SAFETY AND HANDLING

Screenfix should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses. This product should be used in a well ventilated area.

Please consult the information on **The Safety and Handling of Screenfix** in the Chaiyaboon Material Safety Data Sheet.

ENVIRONMENTAL INFORMATION

Screenfix:

- Does not contain heavy metals.

TECHNICAL SERVICE AND INFORMATION

For further information or other relevant data, please do not hesitate to contact us. Chaiyaboon Brothers Company (CBC) has a team of well-trained personnel who are ready to give help and advise regarding product information and application.

