

GHOST REMOVER SCREEN (SSC003)

Main Characteristics

Product Characteristics

Paste/Light Brown colour

Instruction for use

- Clean off all ink residue prior to stencil removal.
- Remove stencil with recommended Screenstrip Powder (SST002)
- Apply a small amount of Ghots Remover Screen (SSC003) to both side of the wet mesh with a brush, thoroughly covering the stained areas in a circular motion.
- Leave to stand for 10-15 minutes. If left to stand for longer periods,
 Ghots Remover Screen can damage the fibres of the mesh.
- Rinse off residue with gently water spray.
- Remove stain with high pressure stripper.

Important

• Stir well before use.

Features

- Use in the screen printing industry for effective removal of hazes and ghost images commonly after left stencil reclaiming.
- Fast acting and highly effective at removing ghost images and stain on all types of mesh.
- May also be used to degrease and chemically abrade new or used aluminum frames perior to mesh stretching.

Standard Packing

5 Kg and 1 Kg

Safety and Handling

- Is free from any toxic, carcinogenic, mutagenic and reprotoxic chemicals.
- Does not have a flashpoint and is, therefore, exempt from the Highly Flammable Liquid Regulations.
- SSC003 should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Should be stored away from children.
- Comprehensive information on the Safety and Handling of Ghost Remover Screen in Safety Data Sheet.

Storage

• Ghost Remover Screen should be stored in a cool dry place at 20-25 °C.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand

SSC003 can be stored for 24 months.

CHAIYABOON BROTHERS CO., LTD.

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com e-mail:sale_cb@cbg.in.th



Tel: +662-533-2533, +662-994-5199 Fax: +662-994-2449, +662-994-5180









Certified Standards

• SSC003 is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.



Ghost Remover Screen SSC003 1-1902