



DEGREASER PLUS (P-6419)

Main Characteristics

Product Characteristics

Gel/ light brown colour

Instruction for use

- Soak the screen with water.
- Use the soft brush to apply some of the Degreaser plus P-6419 onto the screen mesh and rub in a circular motion.
- With a circular motion, rub into the mesh and ensure the entire screen area is treated.
- Leave for a few minutes.
- Use a strong water jet or high pressure water gun to remove the Degreaser.
- Dry the screen thoroughly before further use.

Important

- Stir well before use.

Features

- For pre-treatment of all mesh used with direct emulsion, capillary and direct/indirect films, on both new and used screens.
- Ensures consistent adhesion, eliminates static, fisheyes and pinholes.
- Easy to operate.

Standard Packing

25 Kg, 5 Kg and 1 Kg

Safety and Handling

- Is free from any toxic, carcinogenic, mutagenic and reprotoxic chemicals.
- Does not have a flashpoint and is, therefore, exempt from the Highly Flammable Liquid Regulations.
- P-6419 should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Should be stored away from children.
- Comprehensive information on *the Safety and Handling of Degreaser Plus* in Safety Data Sheet.

CHAIYABOON BROTHERS CO., LTD.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand
Tel : +662-533-2533, +662-994-5199
Fax : +662-994-2449, +662-994-5180

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com
e-mail : sale_cb@cbg.in.th



Storage

- Storage temperature should not be over 40 °C. It should be stored in a dry location with good ventilation and away from heat or ignition sources.
- When stored under these conditions, It is expected to have a shelf-life of 24 months from the date of manufacture.
- Close the bottle tightly after every use.

Certified Standards

- P-6419 is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.

CHAIYABOON
— inKnovation —

