



HARDENER (PATLY)

Main Characteristics

Product Characteristics

Liquid/Clear red colour

Instruction for use

- Make the stencil as required.
- Dry the screen thoroughly.
- Apply Patly on both sides of the finished stencil with a soft brush or sponge.
- Ensure that both sides of the screen are completely treated.
- Use a fan or allow to air-dry placing it in a drying cabinet.
- Ensure that the entire stencil area is thoroughly dry before use.

Important

- Stencils that have been treated with Patly will be more difficult to remove and will require the use of a high pressure gun after de-coating with Screenstrip.

Features

- For higher water-resistance of direct photostencils.
- Design to use with polyester mesh and is not suitable for nylon mesh.
- Low odor.
- Easy to use.

Standard Packing

25 Kg, 5 Kg and 1 Kg

Safety and Handling

- Is free from any toxic, carcinogenic, mutagenic and reprotoxic chemicals.
- Does not have a flashpoint and is, therefore, exempt from the Highly Flammable Liquid Regulations.
- Patly should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Should be stored away from children.
- Comprehensive information on *the Safety and Handling of Patly* in Safety Data Sheet.

Storage

- Storage temperature should not be over 40 °C. It should be stored in a dry location with good ventilation and away from heat or ignition sources.
- When stored under these conditions, It is expected to have a shelf-life of 24 months from the date of manufacture.
- Close the bottle tightly after every use.

CHAIYABOON BROTHERS CO., LTD.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand
Tel : +662-533-2533, +662-994-5199
Fax : +662-994-2449, +662-994-5180

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com
e-mail : sale_cb@cbg.in.th



Certified Standards

- Patly is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.



CHAIYABOON
— inKnovation —