



SCREENFIX (SFX001)

Main Characteristics

Product Characteristics

Viscous/Red colour

Instruction for use

SFX001 (Screenfix) : SFX002 (Catalyst).

- Mix the Screenfix and Catalyst in a ration of 10:1 by weight.
- Ensure the two parts are mixed in the correct ratio, as lack of or excessive catalyst can lead to poor solvent resistance.
- Ensure that the components are mixed in a clean container.
- Keep the container tightly closed after use to prevent reaction with moisture from the air.
- Do not mix more adhesive than is likely to be used within the 30 min. (approx.) pot-life.
- Keep Screenfix at the normal room temperature. Avoid keeping Screenfix at a temperature lower than 0°C (32°F), as this will cause the product to thicken. Screenfix can be brought back to its normal consistency by bringing it back to room temperature (20°C)

Important

- Shake the Screenfix and Catalyst before use.

Features

SFX001 + SFX002

- 2 component frame adhesive.
- Applicable to metal and wooden frames.
- Easy to use.
- Smooth finish.
- Fast dry.

Standard Packing

Screenfix : 5 ltr. and 1 ltr.

Catalyst : 100 ml.

CHAIYABOON BROTHERS CO., LTD.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand
Tel : +662-533-2533, +662-994-5199
Fax : +662-994-2449, +662-994-5180

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com
e-mail : sale_cb@cbg.in.th



Safety and Handling

- Is free from any toxic, carcinogenic, mutagenic and reprotoxic chemicals.
- Does not have a flashpoint and is, therefore, exempt from the Highly Flammable Liquid Regulations.
- SFX001 and SFX002 should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Should be stored away from children.
- Comprehensive information on *the Safety and Handling of Screenfix* in Chaiyaboon Safety Data Sheet.

Storage

- Storage temperature should not be over 40 °C. It should be stored in a dry location with good ventilation and away from heat or ignition sources.
- When stored under these conditions, It is expected to have a shelf-life of 24 months from the date of manufacture.
- SFX002 can be stored for 12 months.
- Close the bottle tightly after every use.

Certified Standards

- Screenfix and Catalyst is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.

