



RUBBER STAR INK (RBS)

Main Characteristics

Ink Type

One Pack / Water-Based

Drying

- Jet dry : 3-5 minutes
- Air dry : 10-15 minutes
- Final step oven : 130-140 °C for 3-5 minutes

Thinning

- 5-10 % water

Cleaning

- Water
- For heavy ink stains, Screensolve (SSO038) can be used.

Mesh

- P36-90 to P61-64 Monofilament

Stencil Type

- All water resistant direct Emulsion photo-stencils

Recommended

- T326 Diazol Tex
- FT426 Polyzol Tex

Application

- Light and dark shade fabrics made wholly or partly of natural fibres such as cotton.

Caution

- Stir well before use.
- It is advisable that the ink be tested fully prior to printing.

Colours Range

15 Colours : 15 Standard colours

Features

- Suitable for light and dark shade fabrics made wholly or partly of natural fibres such as cotton.
- The ink film is extremely elastic with a smooth soft feel like rubber and is resistant to cracking.
- High opacity.
- Long lasting colour brightness.
- Excellent wash resistance.

Available Colours

Standard Colours

RBS100 Black	RBS340 Mid Chrome	RBS590 Violet	RBS720 Brilliant Green
RBS200 White	RBS400 Light Orange	RBS623 Mid Blue	RBS721 Bright Green
RBS201 Opaque White	RBS520 Scarlet	RBS624 Royal Blue	RBS791 Light Brown
RBS320 Light Yellow	RBS540 Deep Red	RBS645 Navy Blue	RBS090 Clear

Standard Packing


30 Kg, 5 Kg and 1 Kg container.

CHAIYABOON BROTHERS CO., LTD.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand
 Tel : +662-533-2533, +662-994-5199
 Fax : +662-994-2449, +662-994-5180

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com
 e-mail : sale_cb@cbg.in.th



Safety and Handling

- All colours comply with the following standards : EN71-3, Standard of The European Economic Community and Part1303, Title16, Code of Federal Regulation of U.S.A.
- Whilst working with the ink, the consumption of food and drink, and smoking are not recommended.
- RBS ink should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Comprehensive information on **the Safety and Handling of RBS ink** in Safety Data Sheet, available on request.

Storage

- Storage temperature should not be over 40 °C. It should be stored in a dry location with good ventilation and away from heat or ignition sources.
- When stored under these conditions, It is expected to have a shelf-life of 24 months from the date of manufacture.
- Close the bottle tightly after every use.

Certified Standards

- RBS ink is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.

