



## SCREENSOLVE (SSO038)

### Main Characteristics

#### Product Characteristics

Liquid/Clear Colour

#### Instruction for use

For washing up and decoating screens

- Clean both sides of the screen with a rag soaked in Screensolve to remove all ink residues.
- Rinse off the screen with water to remove the solvent.
- Apply Screenstrip solution on the both sides of the screen.
- For stubborn stains, reapply the Screenstrip solution and then rinse the screen with water.
- To remove light stains apply Screensolve thoroughly on both sides of the wet screen.
- Allow to react for about three to five minutes.
- Rinse off thoroughly with water before using a high-pressure water gun and allow the screen to dry.

For stain removal from screens

- Apply Screensolve (1 part) to the screen with a rag and add Screenpaste (1 part) to both sides of the mesh using a brush.
- Mix the two products in a circular motion, working the mixture into the screen.
- Allow the screen to stand for 15 minutes.
- Longer periods can damage polyester mesh.
- Rinse off thoroughly with water before using a high-pressure water gun and allow the screen to dry.

### Features

- For the removal of ink residues and mesh stains,
- Use with screenpaste helps remove ghost images and other stains caused during screen printing.
- Enhanced performance when use with Screenpaste.

### Standard Packing

25 Kg, 5 ltr and 1 ltr

### Safety and Handling

- SSO038 should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Should be stored away from children.
- Comprehensive information on *the Safety and Handling of Screensolve* in Safety Data Sheet.

#### CHAIYABOON BROTHERS CO., LTD.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand  
Tel : +662-533-2533, +662-994-5199  
Fax : +662-994-2449, +662-994-5180

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com  
e-mail : sale\_cb@cbg.in.th



**Storage**

- Storage temperature should not be over 40 °C. It should be stored in a dry location with good ventilation and away from heat or ignition sources.
- When stored under these conditions, It is expected to have a shelf-life of 24 months from the date of manufacture.
- Close the bottle tightly after every use.

**Certified Standards**

- SSO038 is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.

